



| Item N. | Descrizione Nuova - Jan04 | Description New - Jan04 | Q.ta Q.ty | Codice - Code | | | | | | | | | |
|---------|--------------------------------------|--|--------------|-----------------------------|-----------------------------|-----------------------------|------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|--|
| | | | | OS630T405 (OS6400T534/B) | OS637T405 (OS6500T534/B) | OS655T405 (OS6750T534/B) | OS675T405 (OS61000T534/B) | OS6110T405 (OS61500T534/B) | OS6150T405 (OS62000T534/B) | OS6185T405 (OS62500T534/B) | OS6220T405 (OS63000T534/B) | OS6300T405 (OS64000T534/B) | |
| | | | | 107041593 | 107041603 | 107041613 | 107041623 | 107041633 | 107041643 | 107041653 | 107041663 | 107041673 | |
| | | | | 3 kW (4HP) | 3,7 kW (5HP) | 5,5 kW (7,5HP) | 7,5 kW (10HP) | 11 kW (15HP) | 15kW (20HP) | 18,5 kW (25HP) | 22 kW (30HP) | 30 kW (40HP) | |
| 1 | Camicia esterna | Motor housing | 1 | 166402750 | | 166402770 | | 166403980 | 166403990 | 166404380 | 166404390 | 166404400 | |
| ** 2 | Statore avvolto DOL | Wound stator, DOL | 1 | 150803123 | | 150803133 | 150803143 | 150803153 | 150803173 | 150803183 | 150803193 | 150803203 | |
| 3 | Albero con rotore | Shaft with rotor | 1 | 155008510 | | 155008520 | | 155008540 | 155008550 | 155007410 | 155007420 | 155007430 | |
| 4 | Supporto superiore | Upper bracket | 1 | | | | | 161452020 | | | | | |
| 5 | Supporto cuscinetto inf. | Lower bearing housing | 1 | | 161452940 | | | 161452950 | | | 161452960 | | |
| 6 | Anello bloccaggio polmone | Diaphragm locking ring | 1 | | | | | 168620200 | | | | | |
| 7 | Fondello | Bottom cap | 1 | | | | | 164250010 | | | | | |
| 8 | Protezione fondello | Bottom cup protection | 1 | | | | | 164201250 | | | | | |
| * 9 | Cuscinetto inferiore | Lower bearing | => | | | 1 - 002311006 | | | 2 - 002311208 | | 2 - 002311210 | | |
| * 10 | Cuscinetto superiore | Upper bearing | 1 | | | | | 002310312 | | | | | |
| 11 | Distanziale | Spacer | 3 | | | | | 162502600 | | | | | |
| 12 | Flangia per supp. superiore | Upper bracket flange | 1 | | | | | 161001210 | | | | | |
| 13 | Tenuta meccanica - parte fissa | Mechanical Seal - stationary part | 1 | | | | | 002229141 | | | | | |
| | Tenuta meccanica - parte rotante | Mechanical Seal - rotating part | 1 | | | | | 002228541 | | | | | |
| 15 | Inserto per labirinto | Sand slinger | 1 | | | | | 168561020 | | | | | |
| * 16 | OR superiore | Upper OR | 1 | | | | | 002221333 | | | | | |
| * 17 | OR inferiore | Lower OR | 1 | | | | | 002221334 | | | | | |
| * 18 | Polmone | Diaphragm | 1 | | | | | 169360122 | | | | | |
| 19 | Protezione fili motore | Wires protection | 1 | | | | | 164260510 | | | | | |
| 20 | Ralla | Washer | 1 | | | | | 168300490 | | | | | |
| 21 | Ghiera fissaggio supp. superiore | Fixing ring for upper bracket | 1 | | | | | 167000110 | | | | | |
| 22 | Piastrina pressacavo | Cable gland plate | 1 | | | | | 168100300 | | | | | |
| 23 | Stringicavo | Cable stop | 1 | | | | | 168560700 | | | | | |
| 24 | Tassello pressacavo | Cable gland | 1 | | | | | 168560751 | | | | | |
| | Rondelle | Washers | 2 | | | | | 168560830 | | | | | |
| ** 25 | Cavo alimentazione | Supply cable | 1 | | | 166993250 (3 m) | | | 166993260 (3 m) | | 166994750 (4 m) | | |
| 26 | Tirante | Tie rod | 4 | | | | | 167101511 | | | | | |
| | Dado | Nut | 4 | | | | | 167000100 | | | | | |
| 28 | Tappo di riempimento | Filling plug | 2 | | | | | 168420130 | | | | | |
| * 29 | OR per tappo | OR for plug | 2 | | | | | 002221102 | | | | | |
| 30 | Coperchio per labirinto | Labyrinth seal cover | 1 | | | | | 164000820 | | | | | |
| 31 | Anello di tenuta | Seal ring | 1 | | | | | 002220820 | | | | | |
| | Supporto sup. c/cavo alim.(4, 22-25) | Upper bracket w/ supply cable (4, 22-25) | 1 | | | 141160330 | | | 141160340 | | 141160760 | | |

Motore Somm. 6" - 6" Sub Motor : OS6T405-SD Serie - Series

| Item N. | Descrizione | Description | Q.ta Q.ty | Codice - Code | | | | | | | | | |
|---------|-------------------------------------|---|--------------|----------------------------------|----------------------------------|----------------------------------|-----------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|--|
| | | | | OS630T405-SD (OS6400T53/B-SD) | OS637T405-SD (OS6500T53/B-SD) | OS655T405-SD (OS6750T53/B-SD) | OS675T405-SD (OS61000T53/B-SD) | OS6110T405-SD (OS61500T53/B-SD) | OS6150T405-SD (OS62000T53/B-SD) | OS6185T405-SD (OS62500T53/B-SD) | OS6220T405-SD (OS63000T53/B-SD) | OS6300T405-SD (OS64000T53/B-SD) | |
| | | | | 107041596 | 107041606 | 107041616 | 107041626 | 107041636 | 107041646 | 107041656 | 107041666 | 107041676 | |
| | | | | 3 kW (4HP) | 3,7 kW (5HP) | 5,5 kW (7,5HP) | 7,5 kW (10HP) | 11 kW (15HP) | 15kW (20HP) | 18,5 kW (25HP) | 22 kW (30HP) | 30 kW (40HP) | |
| *** 2 | Statore avvolto SD | Wound stator, SD | 1 | 150803126 | | 150803136 | 150803146 | 150803156 | 150803176 | 150803186 | 150803196 | 150803206 | |
| 4 | Supporto superiore 2 uscite | Upper bracket 2 outlets | 1 | | | | | 161452560 | | | | | |
| *** 25 | Cavo alimentazione | Supply cable | 1 | | | | 166993250 (3 m) | | | | 166994750 (4 m) | | |
| | Supporto sup. 2 uscite c/cavo alim. | Upper bracket 2 outlets w/ supply cable | 1 | | | | 141160460 | | | | 141160760 | | |

* Parti di ricambio consigliate - Recommended spare parts

** Tensione - Voltage DOL : 380-415 V - 50 Hz

*** Tensione - Voltage SD : 380-415/660 V - 50 Hz

