


TENUTA MECCANICA MECHANICAL SEAL



L10W 10" Submersible Motors

3~ 380-415 50				3~ 400/690 50			
DOL				SD			
930T405	1100T405	1300T405	1500T405	930T405	1100T405	1300T405	1500T405
507006010	507006020	507006030	507006040	507006015	507006025	507006035	507006045
93 kW	110 kW	130 kW	150 kW	93 kW	110 kW	130 kW	150 kW

Component

1	Sand guard	568600060	All models						
2	Mech seal cover	564000040	All models						
* 3	Lip seal	-							
8	Stator assy w/cable	540640640	540640650	540640660	540640670	540640645	540640655	540640665	540640675
	PVC Wire Code	573325815	573325816	573325818	573325815	573325815	573325816	573325818	573325815
	PVC Wire Type	D1,9/2,7	D2,0/2,9	D2,2/3,2	D1,9/2,7	D1,9/2,7	D2,0/2,9	D2,2/3,2	D1,9/2,7
	Tot wire need [m]	915	830	860	1310	915	830	860	1310
9	Key	572650339	All models						
16	Dragging dowel	562200020	All models, 2 pcs						
18	Bottom cover	564250030	All models						
*19	Diaphragm	562360050	All models						
20	Adjusting screw	567200300	All models						
21	Locking nut	572633218	All models						
22	Filling valve	549300020	All models						
24	Thrust bearing bracket	561450130	All models						
26	Stop ring	572651133	All models						
*27	Bearing bush	562590050	All models, 4 pcs						
28	Lower bracket	561450140	All models						
30	Shaft w/rotor	555080640	555080650	555080660	555080670	555080640	555080650	555080660	555080670
31	Upper spacer	562550070	562550070	562550070	562550070	562550080	562550080	562550080	562550080
32	Release valve	549300010	All models						
34	Upper bracket	561450150	All models						
39	Journal sleeve chroma	562800030	All models, 4 pcs						
40	Up thrust washer	568360040	All models						
42	Key	572650469	All models						

Kit

* ->	4 - 5	Cable glands	5KL30AAT	Cable section 1x25-35 (mm2)
* ->	4 - 5	Cable glands	5KL30AAU	Cable section 1x50-70 (mm2)
* ->	9, 10, 12-15, 26	Thrust bearing	5KL41AAB	All models
* ->	23, 25, 29, 33	ORings	5KL02AAC	All models
->	9, 17, 35-37, 41-42	Screws	5KL40AAC	All models
->	38	Repair set	5KL35AAB	FOR REPAIRS ONLY (Journal sleeve chromate, shaft seal ring)

Power cable ACS approved

Section mm2	code / m	suitable for:	Total qty required incl. ground cable	
			DOL	SD
1x25	572851268			93-110-130 KW
1x35	572851270		93 KW	150 KW
1x50	572851272		110 - 130 KW	
1x70	572851274		150 KW	
			25 m	40 m

Mechanical seal, items 52, 54

Ceramic/carbon/NBR	5KL01AAE	Standard motor
Sic / Sic / NBR	5KL01AAF	Special version

Power cable ACS approved lenght standard: 5,5 m

Section mm2	code	suitable for:	Total qty required incl. ground cable	
			DOL	SD
1x25	556990040			93-110-130 KW
1x35	556990050		93 KW	150 KW
1x50	556990060		110 - 130 KW	
1x70	556990070		150 KW	

L10W HT 10" Submersible Motors

3~ 380-415 50				3~ 400/690 50			
DOL		SD		DOL		SD	
830T405	930T405	1100T405	1300T405	830T405	930T405	1100T405	1300T405
507076010	507076020	507076030	507076040				
83 kW	93 kW	110 kW	130 kW	93 kW	110 kW	130 kW	150 kW

Component

1	Sand guard	568600060	All models				
2	Mech seal cover	564000040	All models				
* 3	Lip seal	-					
8	Stator assy w/cable	54064064B	54064065B	54064066B	54064067B		
	HT/HD Wire Code	573325843	573325845	573325846	573325843		
	HT/HD Wire Type	D1,7/2,7	D1,9/2,9	D2,0/3,1	D1,7/2,7		
	Tot wire need [m]	915	830	860	1310		
9	Key	572650339	All models				
16	Dragging dowel	562200020	All models, 2 pcs				
18	Bottom cover	564250030	All models				
*19	Diaphragm	562360050	All models				
20	Adjusting screw	567200300	All models				
21	Locking nut	572633218	All models				
22	Filling valve	549300020	All models				
24	Thrust bearing bracket	561450130	All models				
26	Stop ring	572651133	All models				
*27	Bearing bush	562590050	All models, 4 pcs				
28	Lower bracket	561450140	All models				
30	Shaft w/rotor	555080640	555080650	555080660	555080670		
31	Upper spacer	562550070	562550070	562550070	562550070	562550080	562550080
32	Release valve	549300010	All models				
34	Upper bracket	561450150	All models				
39	Journal sleeve chroma	562800030	All models, 4 pcs				
40	Up thrust washer	568360040	All models				
42	Key	572650469	All models				

Kit

* ->	4 -5	Cable glands	5KL30AAT	Cable section 1x25-35 (mm2)
* ->	4 - 5	Cable glands	5KL30AAU	Cable section 1x50-70 (mm2)
* ->	9,10,12-15,26	Thrust bearing	5KL41AAB	All models
* ->	23, 25, 29, 33	ORings	5KL02AAC	All models
->	9,17,35-37,41-42	Screws	5KL40AAC	All models
->	38	Repair set	5KL35AAB	FOR REPAIRS ONLY (Journal sleeve chromate, shaft seal ring)

Power cable		ACS approved		Total qty required		
Section mm2	code / m	suitable for:	DOL	SD	incl. ground cable	
1x35	572851270		83 KW		DOL	SD
1x50	572851272		93 - 110 KW		25 m	40 m
1x70	572851274		130 KW			

Mechanical seal, items 52, 54

Ceramic/carbon/NBR STD	5KL01AAE	Standard motor
Sic / Sic / NBR	5KL01AAF	Special version

Mechanical seal, ACS approved lenght standard: 5,5 m

Section mm2	code	suitable for:	DOL	SD
1x35	556990050		83 KW	
1x50	556990060		93 - 110 KW	
1x70	556990070		130 KW	

xylem

