

**MOTOR 40S/B SERIES: DIMENSIONS AND WEIGHTS - 2 pole 50Hz**

MOTORE TIPO MOTOR TYPE	POTENZA NOMINALE		DIMENSIONI Max mm	PESO MOTORE	PESO OLIO
	RATED POWER		DIMENSIONS Max mm	MOTOR WEIGHT	OIL WEIGHT
	kW	HP	A	Kg	Kg
40S03M235/B	0,37	0,5	355	7,1	0,73
40S03T405/B			334	6,6	0,68
40S05M235/B	0,55	0,75	355	7,7	0,66
40S05T405/B			355	7,1	0,69
40S07M235/B	0,75	1	380	8,8	0,68
40S07T405/B			355	7,7	0,6
40S11M235/B	1,1	1,5	415	10,7	0,88
40S11T405/B			380	8,8	0,66
40S15M235/B	1,5	2	450	12,3	0,9
40S15T405/B			415	10,9	0,86
40S22M235/B	2,2	3	500	14,6	0,88
40S22T405/B			450	12,4	0,64
40S30T405/B	3	4	450	13,4	0,79
40S40T405/B	4	5,5	570	17,3	1,1
40S55T405/B	5,5	7,5	630	20,8	1
40S75T405/B	7,5	10	836	28,3	1,23

40S-B-2p50\_b\_td\_rev1

Liquido refrigerante: olio bianco minerale atossico acc. FDA standard (es. Pakelo White Oil Fu ISO 15 / approvazione NSF H3)

Cooling liquid: atoxic mineral white oil acc. FDA standardization (ex. Pakelo White Oil Fu ISO 15 / approvation NSF H3)

Dated: 11/2008